

110V GLOBE LIGHT

20W

Pre-wired with 3M Three-Core Yellow Cable and Plug



FEATURES:

- Easy to hold handle for moving light around the site
- Comes with internal socket allowing for multiple 110V lights to be connected up as a circuit
- For use with the Tripod (232025)
- IP54 Weather Resistant
- High Quality
- Robust and Durable Product
- In-built hook on the base to hang the light upside down

APPLICATIONS



CONSTRUCTION



OUTDOOR



WORK SITES

20W

110V GLOBE LIGHT

Pre-wired with 3M Three-Core Yellow Cable and Plug

Part No.	232049
DESCRIPTION	110V Uplight with pre-wired with 3M Three-Core Yellow Cable and Plug
DIMENSIONS	190mm x 190mm x 240mm
BODY COLOUR	Yellow
POWER CONSUMPTION	20W
POWER INPUT	100-120V
COLOUR TEMPERATURE	4000K
COLOUR RENDITION (CRI)	Ra >80
LUMEN OUTPUT/MODES	1800lm
IP RATING	IP54
IK RATING	IK10
CONSTRUCTION	Diecast & PC
WORKING TEMPERATURE	-20°C to +45°C
LIFETIME (HRS)	50,000
SWITCH CYCLES	15,000
CERTIFICATION	UKCA, CE
WARRANTY	1 year (+ 4 year extended warranty with online registration)
EFFICACY RATING	90lm/W




ADDITIONAL ACCESSORIES

Part No.	232025
DESCRIPTION	Tripod for use with Globe Light (232049)
DIMENSIONS	135mm x 135mm x 780mm



BRIGHT SOURCE

**BRIGHT SOURCE**
232049**20**
kWh/1000h

2021 No. 1093