LED PANEL 300 X 300mm



Fits in suspended ceiling grid. Direct replacement for fluorescent luminaires. Installs in minutes!







Available



FEATURES:

- Low maintenance, long-life and eco-friendly design
- Save up to 60% on energy costs over fluorescent
- High-quality light
- Good colour rendition and low glare
- No flickering, no UV, no IR
- Direct replacement for fluorescent luminaries
- In-house testing conducted to ensure quality and reliability

APPLICATIONS









RETA



LED PANEL 300 X 300mm

Fits in suspended ceiling grid. Direct replacement for fluorescent luminaires. Installs in minutes!

Part No.	223276	223283	223290
DESCRIPTION	LED Panel 18W White Frame 3000K	LED Panel 18 W White Frame 4000K	LED Panel 18W White Frame 6000K
DIMENSIONS	295 x 295 x 10mm		
POWER FACTOR	0.92		
POWER CONSUMPTION	18W		
CURRENT	1150mA		
COLOUR TEMPERATURE	3000K (Warm White)	4000K (Cool White)	6000K (Daylight White)
COLOUR RENDITION (CRI)	Ra>80		
LUMENS	1620lm		
LIGHT EFFICACY	90lm/W		
IP RATING	IP20		
BEAM ANGLE	120°		
CONSTRUCTION	PC/ AL/ Steel		
WORKING TEMPERATURES	-20C to +40°C		
ENERGY CONSUMPTION	18kWh/1000hrs		
DRIVER	Bright Source		
CERTIFICATION	UKCA, CE, RoHS		
WARRANTY	1 year (+ 4 years extended warranty with online registration)		

BRIGHT SOURCE

