## 4-IN-1 LED EMERGENCY

## **EXIT SIGN**



- A highly versatile Emergency lighting unit that can be mounted in 4 different ways
- Suspension wires allow the unit to be hung from the ceiling
- Powerful unit that has a viewing distance of 30m
- Slimline, modern design
- IP20 Rated and IK08 Rated for impact
- Conforms to IEC/BS EN 60598-2-22

#### **APPLICATIONS**








FACTORIES OF


WAREHOUSE & STORAGE AISLES


# **4-IN-1 LED EMERGENCY** EXIT SIGN

### A part of the Bright Source Emergency Lighting

Part No.	243182
DESCRIPTION	Maintained emergency version. LiFePO4 battery. 3-4 hours emergency time.
DIMENSIONS	366 x 207 x 84mm
POWER CONSUMPTION	5W
INPUT VOLTAGE	200-240V AC
COLOUR TEMPERATURE	6000K (Daylight White)
LUMENS	70lm
COLOUR RENDITION (CRI)	Ra >80
IP RATING	IP20
IK RATING	IK08
BEAM ANGLE	120°
CONSTRUCTION	Steel/Polycarbonate Panel
WORKING TEMPERATURES	-20°C to +40°C
LIFETIME	30,000hrs
SWITCHING CYCLES	10,000
LUMEN EFFICACY	14lm/W
ENERGY CONSUMPTION	4 kWh
CERTIFICATION	CE, RoHS
WARRANTY	1 year (+ 4 years extended warranty with online registration) <b>Battery 3 years only</b>













BRIGHT SOURCE

243182



G

**5** kWh/1000h

