


LED EMERGENCY EXIT BOX

Complete with Arrow Up Legend



FEATURES:

- Separate legends available (down/left/right)
- 3 hour emergency mode
- Ideal for illuminating exits and walkways in the event of a powercut
- Energy efficient LED exit sign
- Manufactured from a lightweight metal frame
- Ergonomic design
- Robust polycarbonate construction
- Installs with ease
- Self-test button easily accessible to ensure proper operation
- Conforms to emergency standard BS-5499

APPLICATIONS



FACTORIES



OFFICES



WAREHOUSE &
STORAGE AISLES

SLIMLINE LED EMERGENCY EXIT BOX

Complete with Arrow Up Legend



243052



243045

⬆ Exit Box Complete with Up Arrow – 243038
Other legends available separately

⬅ Left Exit Legend for 4w LED Exit Box – 243045

➡ Right Exit Legend for 4w LED Exit Box – 243052

⬇ Down Exit Legend for 4w LED Exit Box – 243069



243038



243069

| Part No. | 243038 |
|------------------------|---|
| DESCRIPTION | Maintained emergency version. LiFePO4 battery. 3-4 hours emergency time. |
| DIMENSIONS | 310 x 195 x 47mm |
| POWER CONSUMPTION | 4W |
| INPUT VOLTAGE | 220-240 VAC |
| COLOUR TEMPERATURE | 6000K (Daylight White) |
| LUMENS | 70lm |
| COLOUR RENDITION (CRI) | Ra >80 |
| IP RATING | IP20 |
| IK RATING | IK08 |
| BEAM ANGLE | 120° |
| CONSTRUCTION | Steel/Polycarbonate Panel |
| WORKING TEMPERATURES | -20°C to +40°C |
| LIFETIME | 30,000hrs |
| SWITCHING CYCLES | 10,000 |
| LUMEN EFFICACY | 14lm/W |
| ENERGY CONSUMPTION | 4 kWh |
| CERTIFICATION | CE, RoHS |
| WARRANTY | 1 year (+ 4 years extended warranty with online registration) Battery 3 years only |




How to Replace the Sign:

Additional signs are made of Polycarbonate and go over the top of the fitting.

1. Open the fitting
2. Replace the sign
3. Close the fitting and secure with screws at the bottom.



Bright Source
243038



4
kWh/1000h



2021 Nov. 1093

BRIGHT SOURCE