

LED 3CCT NON-CORROSIVE FITTING

3CCT Switchable IP65 Rated Batten Fitting - High Lumen Output



Weatherproof



Version Available



Version Available



Version Available



3 Colour Switchable

5
YEAR
WARRANTY
WITH ONLINE
REGISTRATION

FEATURES:

- 3 colour temperature switchable - 3000k, 4000k and 6000k
- IP65 non-corrosive fittings with rustless stainless steel mounting clips and cover clips for simple maintenance
- Push-fit connectors for easy installation
- Strong polycarbonate housing
- Replacement for fluorescent non-corrosive fittings
- Ideal for industrial areas such as garages, car parks and workshops
- Excellent lumen output performance - 120lm/W!

APPLICATIONS



FACTORIES



HOSPITALS



WAREHOUSE &
STORAGE AISLES



WORKSHOPS &
GARAGES

LED 3CCT


NON-CORROSIVE FITTING

3CCT Switchable IP65 Rated Batten Fitting - High Lumen Output

REPLACES

Fluorescent Non-Corrosive Fitting

| Part No. Emergency Part No. | 207467 207528 | 207474 207535 | 207481 207542 | 207498 207559 | 207504 207566 | 207511 207573 |
|--------------------------------|---|-------------------------------|---------------------------------|-------------------------------|---------------------------------|-------------------------------|
| DESCRIPTION | 4ft 19W Single Non-Corrosive | 4ft 30W Twin Non-Corrosive | 5ft 24W Single Non-Corrosive | 5ft 57W Twin Non-Corrosive | 6ft 35W Single Non-Corrosive | 6ft 57W Twin Non-Corrosive |
| DIMENSIONS | 1220 x 88 x 86mm | 1220 x 112 x 86mm | 1520 x 88 x 86mm | 1520 x 112 x 86mm | 1820 x 88 x 86mm | 1820 x 112 x 86mm |
| POWER CONSUMPTION | 19W | 30W | 30W | 50W | 35W | 57W |
| COLOUR TEMPERATURE | 3CCT Colour Switchable - 3000k/4000k/6000k | | | | | |
| INPUT VOLTAGE | AC 220-240V | | | | | |
| LUMENS | 2100l / 2299lm | 3600lm / 3990lm | 2880lm / 3096lm | 6750lm | 4200lm / 4655lm | 6840lm / 7695lm |
| COLOUR RENDITION (CRI) | Ra>80 | | | | | |
| IP RATING | IP65 | | | | | |
| IK RATING | IK10 | | | | | |
| BEAM ANGLE | 120° | | | | | |
| CONSTRUCTION | Polycarbonate/Stainless Steel | | | | | |
| WORKING TEMPERATURES | -20°C to +45°C | | | | | |
| LIFETIME | 50,000 Hours | | | | | |
| SWITCHING CYCLES | 15,000 | | | | | |
| LUMEN EFFICACY | 120lm / 121lm | 120lm / 133lm | 120lm / 129lm | 135lm | 120lm / 133lm | 120lm / 135lm |
| LED TYPE | SMD2835 | | | | | |
| CERTIFICATION | UKCA, CE, RoHS | | | | | |
| WARRANTY | 1 year (+ 4 years extended warranty with online registration) | | | | | |
| UGR RATING | 21.9 | 23.8 | 22.1 | 24 | 22.6 | 25.1 |
| SDCM | <6 | | | | | |
| L VALUE | 70 | | | | | |
| B VALUE | 50 | | | | | |
| LED CHIP BRAND | SAN AN | | | | | |
| DRIVER BRAND | TRIDONIC | | | | | |




OPTION AVAILABLE

BRIGTH SOURCE



Bright Source
Non-Corrosive Battens



57
kWh/1000h



2021 No 109